

Hand hydraulic crimping tool

HCT-185

- 1. Crimping head rotates 360°
- 2. Two stage hydraulic, automatic oressure release
- 3. Super quick, light, durable
- 4. Flip top style for easy access to the fitting



HCT-6022

- 1. Crimping head rotates 360°
- 2. Two stage hydraulic, automatic oressure release
- 3. Super quick, light, durable
- 4. Flip top style for easy access to the fitting



HCT-12042

- 1. Crimping head rotates 360°
- 2. Two stage hydraulic, automatic oressure release
- 3. C-head with 42mm opening width for easy access to the fitting
- 4. Suitable for crimping cable terminal, C-clamp, connector and overhead line



EP-431

- 1. Crimping head rotates 180° , suitable for various working angles
- 2. Two stage hydraulics, automatic pressure release
- 3. C-shaped opening jaw design



EP-510C

- 1. Crimping head rotates 180° , suitable for various working angles
- 2. Two stage hydraulics, automatic pressure release
- 3. C-shaped opening jaw design



	HCT-185	HCT-6022	HCT-12042	EP-431	EP-510C
Crimping Force	5t	6t	12t	12t	13t
Stroke	15mm	17mm	42mm	31mm	38mm
Rated Pressure	700bar	700bar	700bar	700bar	700bar
Cimping Capacity	Max. 185mm²	Max. 300mm²	Max. 400mm²	Max. 300mm²	Max. 400mm²
Net Weight	2kg	3.8kg	6.1kg	6.2kg	7.8kg
Standard Dies	Cu10-185mm²	Cu50-300mm²	Cu70-400mm²	Cu50-300 mm²	Cu70-400 mm²
Dimensions	37*13*6cm	50*17*7cm	56*17*7cm	67*17*9cm	67*17*9cm
PP Plastic case	51*22*11cm	51*22*11cm	51*22*11cm	51*22*11cm	51*22*11cm

Hand hydraulic crimping tool

BQK-70

- 1. Crimping head rotates 180°
- 2. High-density clamp head, stronger pressure
- 3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm
- 4. C-shaped opening jaw design



BQK-120

- 1. Crimping head rotates 180°
- 2. High-density clamp head, stronger pressure
- 3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm



BQK-240

- 1. Crimping head rotates 180°
- 2. High-density clamp head, stronger pressure
- 3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm



BQK-300

- 1. Crimping head rotates 180°
- 2. High-density clamp head, stronger pressure
- 3. Two-speed oil inlet design, leak-proof and durable, stable operation, Safe and firm



HCT-6030

Dieless hand hydraulic crimping tools

- 1. Crimping head rotates 180° , suitable for all working angles
- 2. Two stage hydraulics, automatic pressure release
- 3. C-shaped opening jaw design



	BQK-70	BQK-120	BQK-240	BQK-300	HCT-6030
Crimping Force	6t	8t	12t	13t	6t
Stroke	12mm	16mm	20mm	20mm	32mm
Rated Pressure	700bar	700bar	700bar	700bar	700bar
Crimping Capacity	Max. 70mm²	Max.120mm²	Max.240mm²	Max.300mm²	Max. 300mm²
Net Weight	3kg	4.5kg	6.8kg	6.6kg	4.8kg
Standard Dies	Cu4-70mm²	Cu10-120mm²	Cu16-240mm²	Cu16-300 mm²	-