

[Battery powered hydraulic pump](#)

ECT-700



Two stage hydraulic:

Two stage hydraulic, automatic pressure-release

LCD:

External LCD screen, easy to read the cutting times

LED:

With LED light for dark place

Lithium battery:

High-capacity 18V Li-ion battery with power indicator, with fast charger

Lithium battery:

High-capacity 18V Li-ion battery with power indicator, with fast charger

PP plastic, molding in one, strong and fall-resistant

1. It can be equipped with split nut crusher and press joint pliers, cutter and other single - acting tools
2. Pressure gauge is equipped for easy observation of operation



ECT-700

Reservoir Capacity 200mL

Rated Pressure 700bar

Voltage power DC18V

Weight 4kg

Standard 0.6m hydraulic

Accessories hose

Dimensions 38*7*29cm

Packing Platic Case

Packing Size 59*51*14cm

[Pneumatic hydraulic pump](#)
PG-2



1. Excellent pressure holding performance
2. Suitable for non-sparking work environment
4. Built-in silencer significantly reduces noise and reduces personnel fatigue
5. Air and oil filters reduce pollutant damage to the pump
6. Aluminum alloy body and outer casing, durable and light
7. Built-in relief valve prevents overload operation
8. Unique needle valve guides pressure relief

PG-2

Reservoir Capacity 1.6L

Output Pressure 700bar

Oil Delivery at 0.12(0.8)L/min
high(low) Pressure

Weight 8.6kg

Packing Carton/Wooden case

[Double action gasoline engine pump](#)

HPG-700



Large oil capacity, suitable for large capacity crimping tools and longtime operation without engine overheating

High and low double-speed automatic switch, well fit for single and double action tools such as 60t, 100t, 200t and 300t

Rated output pressure 70Mpa, maximum up to 85Mpa

Retract pressure protection system & overflow

protection valve, safe and reliable

Low noise, environment friendly

Equipped with pressure gauge for pressure reading

[Remote control double action gasoline engine pump](#)

HPG-700MX



HPG-700

HPG-700MX

Reservoir Capacity 10L

10L

Rated Output Pressure 700bar

700bar

Oil Delivery at High (Low)Pressure 1.2(7.5)L/min

1.2(7.5)L/min

Engine Speed 3600rpm

3600rpm

Size 650x370x500mm

650x370x500mm

Weight 50kg (Oil not included)

52kg(Oil not included)

Packing Carton/ Wooden case

Carton/ Wooden case

Product Catalogue>>Angle Steel

Class 1

-- Nut breaker --

/41/	Battery powered nut splitter	10t	M8-M24
/41/	Battery powered nut splitte	10t	M8-M24
/41/	Hydraulic nut splitter	12t	M8-M24
/41/	Mechanical nut splitter	/	4-17mm
/41/	Mechanical nut splitter	/	8-24mm
/41/	Mechanical nut splitter	/	19-36mm

Class 2

-- Hydraulic nut splitter --

/42/	Hydraulic nut splitter	M6-M12	10-19mm
/42/	Hydraulic nut splitter	M12-M16	19-24mm
/42/	Hydraulic nut splitter	M16-M22	24-32mm
/42/	Hydraulic nut splitter	M22-M27	32-41mm
/42/	Hydraulic nut splitter	M27-M33	41-50mm

Class 3

-- Hydraulic angle steel cutting tool --

/42/	Hydraulic angle steel cutting tool	23t	75*75*8mm
/42/	Hydraulic angle steel cutting tool	45t	110*110*10mm