

Battery powered cutting tool

Head 360°: Flip to style, head rotates 360°
Two stage hydraulic: Two stage hydraulic, automatic pressure-release
LCD screen: External LCD screen, easy to read the cutting times
LED: With LED light for dark place
Lithium battery: High-capacity 18V Li-ion battery, with quick charger
PP Plastic case: PP plastic, molding in one, strong and anti-impact
Cutting capacity: The exact cutting capacity depends on the type of cable or rope

ECT-45



ECT-55



Battery powered cutting tool

Head 360°: Flip to style, head rotates 360°
Two stage hydraulic: Two stage hydraulic, automatic pressure-release
LCD screen: External LCD screen, easy to read the cutting times
LED: With LED light for dark place
Lithium battery: High-capacity 18V Li-ion battery, with quick charger
PP Plastic case: PP plastic, molding in one, strong and anti-impact
Cutting ability: For cutting copper and aluminum cables with light weight steel armored (depending on cable type)

ECT-50



ECT-85



ECT-105



ECT-45

	ECT-45	ECT-55
Outout Force	6t	12t
Rated Pressure	700bar	700bar
Cutting Capacity	Max.: Ø45mm Cu/Al/ACSR, Max.: Ø12mm steel bar	Max.: Ø55mm Cu/Al/ACSR, Max.: Ø22mm steel bar
Net Weight	5.5kg	8.3kg
Dimensions	450*70*260mm	510*70*280mm
Packing	Plastic Case	Plastic Case
Packing Size	59*51*14cm	59*51*14cm



Battery level Pressure release button Working Light LCD Rubber handle Air grid Strap buckle

ECT-50

	ECT-50	ECT-85	ECT-105
Outout Force	6t	6t	12t
Rated Pressure	700bar	700bar	700bar
Cutting Capacity	Max.: Ø50mm Cu/Al 10kV single-core cable 400mm ²	Max.: Ø85mm Cu/Al Max.: (10kV)3x185mm ² armored cable	Max.: Ø105mm Cu/Al Max.:(10kV)3x300mm ² armored cable
Net Weight	4.2kg	6.7kg	10.7kg
Dimensions	440*70*280mm	550*70*280mm	640*90*280mm
Packing	Plastic Case	Plastic Case	Plastic Case
Packing Size	59*51*14cm	59*51*14cm	66*48*12.5cm



Battery level Pressure release button Working Light LCD Rubber handle Air grid Strap buckle