

### Hydraulic cutting tool

- Two stage hydraulic:** Two stage hydraulics, automatic pressure-release
- Easy operation:** Fast cutting, light weight, easier for cutting
- Head 360° :** Flip top, cutting head rotates 360°
- Quick hand release:** Hand release button, release during the operation with quick retraction

**Cutting ability:**

#### HC-45



60kN  
700bar

#### HC-55



120kN  
700bar

### Hydraulic cutting tool

- Two stage hydraulic:** Two stage hydraulics, automatic pressure-release
- Easy operation:** Fast cutting, light weight, easier for cutting
- Head 360° :** Flip top, cutting head rotates 360°
- Quick hand release:** Hand release button, release during the operation with quick retraction
- Cutting ability:** The exact cutting capacity depends on the type of cable or rope

#### HC-50



60kN  
700bar

#### HC-85



60kN  
700bar

### Hydraulic cutting head

#### PC-30C

- C-type opening for easy access to the fitting
- Powered by single acting hydraulic pump
- The exact cutting capacity depends on the type of cable or rope



45kN  
700bar

#### PC-45

- Flip top style for easy access to the fitting
- Powered by single acting hydraulic pump
- The exact cutting capacity depends on the type of cable or rope



60kN  
700bar



60kN  
700bar

#### PC-55

- Flip top style for easy access to the fitting
- Powered by single acting hydraulic pump
- The exact cutting capacity depends on the type of cable or rope



120kN  
700bar

#### PC-55A

- Double circuit oil cylinder reset, efficient and fast, suitable for mass cutting
- Suitable for cutting copper, aluminum cables and ACSR
- Closed cutting head with bolt interlock




120kN  
700bar

	PC-30C	PC-45	PC-55	PC-55A
Outout Force	4.5t	6t	12t	12t
Rated Pressure	700bar	700bar	700bar	700bar
Cutting Capacity	Max. 300mm <sup>2</sup> single core cable Max. 240mm <sup>2</sup> ACSR	Max.: Φ45mm Cu/Al/ACSR Max.: Φ12mm steel bar	Max.: Φ45mm Cu/Al/ACSR Max.: Φ55mm ACSR Max.: Φ12mm steel bar	Max.: Φ55mm ACSR Max.: Φ22mm steel bar Max.: Φ22mm steel bar
Net Weight	3kg	3.8kg	5.5kg	4.5kg
Packing	Canvas Bag	Canvas Bag	Canvas Bag	Canvas Bag
Dimensions	36*10*7cm	36*10*7cm	40*13*8cm	47*15*7cm

### Hydraulic cutting head

#### PC-40

- Cut copper flat wire of transformer
- C-type opening for easy access to the fitting
- Powered by single acting hydraulic pump
- The exact cutting capacity depends on the type of cable or rope



60kN  
700bar

#### PC-40

Outout Force	6t
Rated Pressure	700bar
Cutting Capacity	Max. Φ 40mm flat copper wire
New Weight	3kg
Packing	Canvas Bag
Dimensions	36*10*7cm